



CARBONLESS COPY PAPER

Item 指标		Unit 单位	Specification 标准			Others 其他要求
Basis Weight 定量		g/m ²	Premium 优等	A grade 一等	Qualified 合格	1、纸面:平整洁净,印刷时无明显透印、掉粉掉毛现象; 2、匀度:涂布均匀,无透明点或发花情况等; 3、端面:切边整齐,平整光洁,无毛边现象; 4、外观:无折子、皱纹、褶皱、霉斑、擦痕、裂口、斑点、显色等纸病; 5、标示:外包装设计有明显的产品标示标签; 6、摺件整齐,外贴标签整齐,包装整洁牢固; 7、卷筒纸接头要求:接头数<2个; 8、线长:卷筒纸长按订单要求,且各卷长度标签标识清楚; 1. Paper surface: Smooth and clean, with no obvious print-through, powder or lint loss during printing; 2. Evenness: Even coating, no transparent spots or blooms, etc; 3. End surface: neatly trimmed, smooth and smooth, without burrs; 4. Appearance: No paper defects such as folds, wrinkles, obvious streaks, cracks, spots, discoloration, etc; 5. Labeling: The outer packaging is designed with obvious product identification labels; 6. The stacks are neat, the outer labels are neat, and the packaging is neat and firm; 7. Requirements for joints of roll paper: Number of heads <2; 8. Line length: The length of the reel should be as required by the order, and the length label of each roll should be clearly marked;
Deviation Of Basis Weight 定量偏差	CB CF SC/CB CFB SC	%	≤50.0、50.0-60.0、60.0-90.0、>90.0			
			<+5.0 <+6.0	≤±6.0 <+7.0		
Apparent Density 紧度		g/cm ³	≥0.70	≥0.67		
Brightness 亮度 (白纸)		%	≥85	≥80	≥75	
Opacity 不透明度	<50g/m	%	≥65			
	>50g/m		≥70			
Smoothness (CF Side) 平滑度 (CF面)		s	≥50	≥40	≥30	
pH Value (CF Side) pH值 (CF面)		-	6--9			
Lateral expansion rate 横向伸缩率		%	3.0	3.8	3.8	
Curls(sheet) 翘曲值 (平板)		mm	≤5.0	≤10.0	≤15.0	
Image Performance (Triple Layer) 显色性能 (第三层)	Image Density 显色密度 24h	ΔE	-	≥60	≥55	≥50
		D	-	0.7	0.6	0.5
	Image Sensitivity 显色灵敏度	ΔE	%	80		
		D		85		
Abrasion resistance 耐摩擦性	ΔE	Dynamic 动	%	≤5.0		
		Static 静	-	No obvious color development 无明显显色点		
Light Resistance 耐光性 (ΔE 144h Retention 144h 保留率)		-	≥60	≥50	≥40	
Moisture content of delivery goods (交货水分)		%	6.5±2.0			